

HYUNDAI



HX245L Efficiency pioneer, loading model

Rated Power 141.4kW/2,000rpm Operating Weight 24,500kg Bucket Capacity 1.4m³

HX245L

ENGINE	Manufacturer	-	HYUNDAI
	Model	-	DL06
	Emission Standard	-	TIER 4
	Rated Power(gross)	kW/rpm	141.4/2,000
	Piston Displacement	cc	5,890
	No.of cylinder-Bore×stroke	EA-mm	100X125
	Battery	EA-V×AH	24 x 100
SPECIFICATIONS	Swing Speed	rpm	11.1
	Travel Speed	km/hr	6.2/3.3
	Max.Drawbar Pull	ton	22.5
	Bucket Digging Force(ISO)[Boost]	ton	15.1
	Arm Digging Force(ISO)[Boost]	ton	11.1
UNDERCARRIAGE	Carrier Rollers	EA(Each Side)	2
	Track Rollers	EA(Each Side)	9
	No.of Track Shoes	EA(Each Side)	51
	Ground Pressure	kgf/cm ²	0.58

DIMENSIONS	Boom Length	mm	5,700
	Arm Length	mm	2,900
	Bucket Capacity	m ³	1.4
	Overall Length	mm	9,571
	Overall Width	mm	3,200
	Upper width	mm	2,709
	Overall Height of Boom	mm	3,005
	Overall Height of Cab	mm	2,996
	Track Gauge	mm	2,600
	Track Length	mm	4,630
	Track shoe Width	mm	600
	Min.Ground Clearance	mm	427
	Ground Clearance of Counterweight	mm	1,076
OTHERS	Tail Swing Radius	mm	2,855
	Fuel Tank	l	400
	Hydraulic Tank(System)	l	196
	Engine Oil	l	29
	Engine Coolant	l	30
	Urea Tank	l	45

* This sample may contain optional configurations, painting styles, and design changes

