

HYUNDAI



HX130 PIONEER OF WEALTH CREATION

Rated Power 75kW/2,400rpm Operating Weight 13,055kg Bucket Capacity 0.53m³

HX130

ENGINE	Manufacturer	-	HYUNDAI	UNDERCARRIAGE	Carrier Rollers	EA(Each Side)	1
	Model	-	DN03		Track Rollers	EA(Each Side)	7
	Rated Power(gross)	kW/rpm	75/2,400		No.of Track Shoes	EA(Each Side)	40
	Piston Displacement	cc	3409		Ground Pressure	kgf/cm ²	0.47
	No.of cylinder-Bore×stroke	EA-mm	4-98x 113	DIMENSIONS	Overall Length	mm	7,730
	Battery	EA - V x AH	2- 12V x 100Ah		Overall Width	mm	2,540
WORKING DEVICE	Boom Length	mm	4,600		Overall Height of Cab	mm	2,755
	Arm Length	mm	2,260		Track Gauge	mm	1,990
	Bucket Capacity	m ³	0.53		Tumbler Distance	mm	2,780
SPECIFICATIONS	Swing Speed	rpm	10		Overall Length of Crawler	mm	3,486
	Swing Torque	kN.m	35.3		Track shoe Width(OPT)	mm	500
	Travel Speed	km/hr	3.1/5,1		Min.Ground Clearance	mm	414
	Gradeability	deg	35		Ground Clearance of Counterweight	mm	875
	Bucket Digging Force(ISO)	ton	9.7/10.5	WORKING RANGE	Max. Digging Reach	mm	7,937
	Arm Digging Force(ISO)	ton	6/6,4		Max. Digging Depth	mm	5,366
OTHERS	Fuel Tank	l	265		Max. Digging Height	mm	8,338
	Hydraulic Tank(System)	l	145		Max. Unloading Height	mm	6,001
	Operating Weight	kg	13,055		Min. Swing Radius	mm	2,417

* This sample may contain optional configurations, painting styles, and design changes